



COPY OF PAPERS  
ORIGINALLY FILED

**Marked Up Version Showing Changes**

48. (Twice Amended) The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having a polygonal cross-sectional configuration with a length of 0.5 inches to 3 inches.
53. (Amended) The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having a substantially circular cross-sectional configuration and a diameter of 0.5 inches to 3 inches.
54. (Amended) The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having a square cross-sectional configuration with a width of 0.5 inches to 3 inches.
55. (Amended) The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having an elliptical shape and a major axes of 0.5 inches to 3 inches.
56. (Amended) The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having an elliptical shape and a minor axes of 0.5 inches to 3-2 inches.
57. The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having a rectangular shape with a length of about 0.5 inches to 3 inches.
58. The method of fluid distribution of claim 47, including a step of utilizing ceramic filter units having a rectangular shape with a width of about 0.5 inches to 3 inches.

RECEIVED  
MAY 01 2002  
10 1700